NDIA - 29th Environmental and Energy Symposium & Exhibition



USAREUR Facilities Class I ODC Elimination Program

Integrating Class I ODC Elimination with Project Programming





Presented by:

• Raymond K. Best, P.E., Buchart-Horn Inc.

Prepared by:

- Ulrich Osberghaus, Dipl.-Ing., Buchart-Horn GmbH
- Kenneth Wrightsman, P.E., IMA-EUROPE
- Andrew Jantzer, P.E., Buchart-Horn, Inc.



DA Policy - Elimination of Class I ODCs at Army Installations

- Policy
 - Class I ODCs must be eliminated from all facilities on Army Installations by the end of FY 2003*
- Installation Commanders
 - Responsible for Class I ODC Elimination
- Tenant Commanders
 - Responsible for Complying with Installation Class I ODC Policies

^{*} As of 22 Nov 2002 Elimination of Class I ODC no longer required

Legal background

- Class I ODCs on USAREUR Installations are restricted by
 - US Federal Laws
 - Army Regulations
 - European Union Guidelines
 - Host Nation Laws



Legal background

- US-Public Law 102-484
- Final Governing Standards (FGS)
- European Regulations 3613/00 and 2037/00
- German "FCKW Halon-Verbots-Verordnung"



Background

- USAREUR, ODCSENGR Environmental Branch
 - Develop plans and funding projects for the elimination of Ozone Depleting Chemicals (Class I ODCs) throughout Europe
- US Army Corps of Engineers, Europe District
 - Contracting Agent
 - Technical Review
- Buchart-Horn GmbH
 - Local Knowledge
 - Environmental Expertise



- Method
 - Single Task Order
 - USAREUR Wide
 - 3 Major Activities
 - Identification
 - Programming
 - Reporting

Requirements

- Investigate legal and regulatory background
- Identify Class I ODC containing equipment
- Determine replacement & retrofitting projects
- Estimate replacement removal costs
- Prioritize equipment and prepare plans
- Enter Class I ODC replacement projects into EPR
- Prepare EPR Roll-up files
- Submit Class I ODC Elimination Plans

- The program execution included a prototype phase
 - Prototype phase tested
 - initial standards
 - procedures
 - Prototype phase allowed the Government Working Group to refine the methodology

- 21 Base Support Battalions (BSB)
- 120+ Installations
 - Germany
 - Belgium
 - Netherlands
 - Italy




- Inspection
 - Physical inspection
 - Existing record review
- Simultaneous Visits by Survey Teams at each
 BSBs
- Approximately 1 week per BSB

- Typical equipment
 - Refrigeration
 - Air Conditioning
 - Fire Extinguishing Units



- What was found
 - 2900+/- pieces of Class I ODC containing equipment
 - Containing more than 3400 kg (7480 lbs) Class I ODCs

Typical Equipment



Cooling Unit



Walk-in Fridge

Typical Equipment



6 Door Refrigerator




Cooling Unit

- Equipment assessment:
 - Review of maintenance records
 - Maintenance History
 - Leak Rate
 - Class I ODC Refill
 - Other
 - Visible inspection of the units



- Equipment Condition Assessment Categories
 - Out of operation
 - Poor
 - Average
 - Good

- Out of operation
 - Replaced
 - Removed
- Poor Condition
 - Retrofitted
- 150 pieces of equipment were replaced or retrofitted



- Cost Estimating
 - Each piece of equipment
 - Market Research/Current Prices
 - Local Currency

- Enter Projects into EPR
- Prepare EPR Roll-up files
- Data entry
 - Project information
 - Narrative description
 - Regulatory information

Reporting

- Elimination Plans each ASGs/BSBs
- Elimination plan contains clear guidance for Class I ODC elimination
 - Responsibilities
 - Procedures
 - Resources
 - requirements
- Developed for use as follow up tool to track Class I
 ODC elimination

Reporting

- Elimination Plans consist of 7 Chapters:
 - Information about the Installation
 - Elimination Team
 - Inventory
 - Rules and Regulations
 - Recovery and Turn in
 - Responsibilities
 - Funding Resources

Summary

- USAREUR, ODCSENGR successfully conducted an integrated Class I ODC inventory and elimination program at 21 BSBs in 4 Countries
- Identification, planning and programming activities were combined into a single task order resulting in
 - Rapid Execution
 - Consistency in Reporting/Procedures
 - Solid Basis for Class II survey and Class I resurvey



Future Outlook - USAREUR

- Class II ODC Elimination Program
- Verify Progress of Class I Elimination Program

NDIA - 29th Environmental and Energy Symposium & Exhibition



USAREUR Facilities Class I ODC Elimination Program

Integrating Class I ODC Elimination with Project Programming





- A valve is attached to the flow tube. Valve remains in place for future use.
- R 12, or R 502 is pumped from the reservoir.
- Oil is removed from the reservoir and filter.
- New oil is installed according to the freon selected.
- Close off oil system and low pressure pump for final refrigerant evacuation.
- The cooling system is then cleaned and dried.
- New freon (R 401a, or R402a) is pumped in.
- Standard practice is to fill the gases removed from the refrigeration unit tanks into separate cylinders. Once full, these cylinders are transported to an incineration facility for destruction.



Typical valve



Typical valve & label



Pump Equipment set up



Pumping ODC to cylinder



Refill unit w/new refrigerant

Typical Equipment



Centralized cooling facility



Cooling Room