



Mortar Propulsion FCT Programs

Swiss 120mm Mortar Propelling Charge Austrian Celluloid Mortar Increment Containers

International Infantry & JSSAS Annual Symposium

Atlantic City, NJ May 16-19, 2005

Mr. Wayne Miller US ARMY RDECOM-ARDEC

Research, Development and Engineering COMmand



Mortar Propulsion FCT Programs








Objective: Qualify an extruded-impregnated (EI) propellant for

the U.S. 120mm mortar propulsion system.

Foreign Manufacturer: Rheinmetall/Nitrochemie Wimmis AG



Objective: Qualify celluloid mortar increment containers (MICs) for

the U.S. 60mm and 120mm mortar propulsion systems

Foreign Manufacturer: Kaufman & Gottwald Ges.m.b.h (KAGO)






Sponsor: PEO AMMO / PM CAS

May 2005 1/1

Benefits

- Lower temperature coefficient will result in increased range to meet Future Combat System's (FCS) requirements.
- Lower flame temperature resulting in a reduction of blast over pressure and longer sustained firing.
- Increased stability with a 3 times longer shelf life.
- Diphenylamine (DPA), the stabilizer in M47, is eliminated. This results in environmental compliance with Executive Order 12856 Eliminate or reduce the unnecessary acquisition of products containing extremely hazardous substances or toxic materials. Estimated cost avoidance of \$11M in M47 propellant compliance costs.

Benefits (cont'd)



Accomplishments

- Initiated production of EI main charge propellant candidates for initial evaluation.
- Conducted preliminary ballistic testing of initial propellant candidates.
- Ballistic test results were evaluated and EI main charge propellant downselected.
- Manufactured downselected main charge propellant for initial evaluation testing.

Planned Accomplishments

- Start initial evaluation testing 4Q FY05
- Complete initial evaluation testing 1Q FY06
- Manufacture main charge propellant for qualification testing 2Q FY06
- Qualification testing 3Q FY06

Test and Evaluation

Phase 1: Initial Evaluation- Propelling Charge Test Plan:

Load Swiss EI 120mm mortar propelling charge propellant at Yuma Proving Ground and conduct following preliminary testing as a risk mitigation effort:

Test	Procedure	Test Rds	Control Rds
Charge Assessment		15	-
Uniformity	TOP 4-2-200	60	30
Blast Overpressure	MIL-STD-147B and MTP 4-2-82	2 15	10
Hot and Dry Cycle	ITOP 4-2-820 and TOP 4-2-504	10	5
Cold Soak	TOP 4-2-504	<u>10</u>	<u>5</u>
	Total Round	ls 110	50

Test and Evaluation (cont'd)

Phase 2: Qualification Test Plan:

Load production lot of Swiss EI 120mm mortar propelling charge propellant at Yuma Proving Ground and conduct qualification testing as follows:

<u>Test</u>	Procedure	Test Rds	Control Rds
Velocity and Pressure	TOP 4-2-700	60	20
Secured Cargo Vibration	TOP 1-1-050	40	14
Sequential Rough Handling	TOP 4-2-602	80	28
Hot and Dry Cycle	ITOP 4-2-820 and TOP 4-2-504	24	8
Cold Soak	TOP 4-2-504	24	8
Adverse Condition	AR 70-38, MIL-STD-810 and	60	20
	TOP 4-2-504		
Rate of Fire	MTP 3-2-050	300	
Blast Overpressure	MIL-STD-147B and MTP 4-2-822	2 <u>30</u>	<u>10</u>
	Total Round	s 618	108

6/12

Conclusion

Preliminary results support that EI main charge propellant for the 120mm mortar should achieve the program objective of increased range. In addition, this propellant eliminates the use of a hazardous component and has a shelf life three times longer than the current 120mm main charge propellant.

Benefits

- Cost savings for 60mm and 120mm MICs
- Use of celluloid material has significant potential to improve the robustness of the MIC for semi and auto-loading capability, i.e. FCS application.
- Celluloid MICs provide 100% waterproofing and air tightness.

Accomplishments

- Celluloid MIC drawings completed, reviewed and accepted to meet the performance envelope for U.S. propulsion systems.
- Celluloid MIC tooling certificates were submitted and approved.
- Completed manufacture of both 60mm and 120mm celluloid MIC tooling for US design.
- Met with celluloid sheet manufacturer and sheets were prepared for KAGO's use to manufacture MICs.

Planned Accomplishments

- Manufacture initial evaluation test quantities 4Q FY05
- Conduct initial evaluation testing 1Q FY06.
- Manufacture qualification test quantities 2Q FY06
- Qualification testing 3Q FY06.

Test and Evaluation

Phase 1: Initial Evaluation Test Plan:

Load KAGO 60mm and 120mm MICs at Yuma Proving Ground and conduct following preliminary testing as a risk mitigation effort:

Test	Procedure	Test Rds	Control Rds
Residue and Debris	TOP 3-2-801	30	20
Charge Assessment		15	
Uniformity	TOP 4-2-200	45	20
Rough Handling	TOP 4-2-602	20	10
Adverse Condition	AR 70-38, MIL-STD-810 and TOP 4-2-504	<u>30</u>	<u>15</u>
	Total Roun	ds 140	65

10/12

Test and Evaluation (cont'd)

Phase 2: Qualification Test Plan:

Load KAGO 60mm & 120mm MICs at a Yuma Proving Ground and conduct qualification testing as follows:

<u>Test</u>	Procedure	Test Rds	Control Rds
Residue and Debris	TOP 3-2-801	30	20
Velocity and Pressure	TOP 4-2-700	60	20
Secured Cargo Vibration	TOP 1-1-050	40	14
Sequential Rough Handling	TOP 4-2-602	80	28
Hot and Dry Cycle	ITOP 4-2-820 and TOP 4-2-504	24	8
Cold Soak	TOP 4-2-504	24	8
Adverse Condition	AR 70-38, MIL-STD-810 and	60	20
	TOP 4-2-504		
Rate of Fire	MTP 3-2-050	<u>300</u>	<u></u>
	Total	618	118
Sequential Rough Handling Hot and Dry Cycle Cold Soak Adverse Condition	TOP 4-2-602 ITOP 4-2-820 and TOP 4-2-504 TOP 4-2-504 AR 70-38, MIL-STD-810 and TOP 4-2-504 MTP 3-2-050	80 24 24 60 300	28 8 8 20

11/12

FCT Proposal – Austrian Celluloid MICs

Conclusion

- Celluloid MIC drawings and tooling completed.
- Celluloid MIC manufacturing process is being optimized.
- Initial evaluation and qualification testing scheduled for FY06.