


Greenup L&D

Rodney Cremeans, PE, PS Project Manager/Structural Engineer




Greenup L&D





Greenup L&D





Greenup L&D Statistics

◆ Traffic

- 8th Busiest Lock in United States
- 1995 2004 Average Annual Tonnage = 71.1
 Million Tons
- Projection By 2050 tonnage = 71.9M to 118M

Closures

- 1991 \$5.7M Transportation Delay Costs
- 1998 \$3.6M Transportation Delay Costs
- 1999 \$3.6M Transportation Delay Costs
- 2003 \$13.2M Transportation Delay Costs,
 \$28.6M+ End User Costs, \$1.5M O&M Costs, 546
 tows affected








Greenup L&D Miter Gates







Greenup L&D Miter Gates

Present situation

- Miter gates for main lock chamber are significantly deteriorated
- Unscheduled outage in FY 03 revealed large cracks on the downstream miter gate – main chamber
 - Downstream middle wall leaf has extensive cracking around the pintle casting
 - Upstream river wall leaf had two cracks in the thrust diaphragm (steel member above pintle casting)
- Strain gauges have been installed to assist in monitoring the miter gates
- The gates have severely deteriorated and additional dewatering, inspection, and repair is anticipated



Greenup L&D Project Description

- Project Authorized WRDA 2000
- Project Elements
 - Downstream Mooring Cells
 - Miter Gate Change-out System
 - R.C. Byrd Dry Dock
 - Extend Auxiliary Lock Downstream to 1200'
 - Environmental Mitigation
 - Rehabilitation of Main Lock & Dam Components
- Total Project Cost \$230.2 M
 - Excludes Rehab



Greenup L&D

Rendering of Completed Project





Greenup PED Project Status

- Funding through FY05: \$7.8 M
- Pre-Construction Engineering and Design (PED) Activities
 - Mooring Cells P&S (100%)
 - Lock Extension DDR (10%)
 - Hydraulic Modeling (90%)
 - Drilling (100%)
 - Miter Gate Design (90%)
 - Conducted Preliminary Mitigation Modeling in FY 03



Mitigation Model Study



Navigation Approach Modeling

Greenup L&D




Filling & Emptying System Modeling





Greenup L&D





Greenup L&D Mooring Cells








Greenup L&D Mooring Cells

Concurrent Navigation



Lock and Dam No. 24


1400 cy tremie, then pumped Maximum 100 cy/hour Approx. 20 hours to place concrete

24 hour navigation closure permitted to place concrete, but not used Helper boat for 7 days for concrete strength gain period



Greenup L&D Miter Gate Quick Change-out System

- 1. Assembly pier (18' x 32' x 66')
- 2. Features: Removable Pintle Base, Miter Gate **Blocks, Jack Support** Slabs





Greenup L&D Fixed Downstream Guide Wall












Greenup L&D Supplemental F&E System






Greenup L&D Supplemental F&E System





Greenup L&D Supplemental F&E System






Greenup L&D New Land Wall - Conventional






Greenup L&D Dry Dock at R.C. Byrd L&D





Greenup L&D Dry Dock at R.C. Byrd L&D







Greenup L&D Miter Gate Bay

FLOAT-IN MITER GATE BAY "INNOVATIVE TECHNIQUE"
















Casting of Miter Gate Bay

















PLAN



LONGITUDINAL CROSS SECTION AT R.C. BYRD DRY DOCK









EL. 556

EL. 515

AT R.C. BYRD DRY DOCK








AT R.C. BYRD DRY DOCK



Greenup L&D Miter Gate Bay




Remarks:

- 1. Case 1: Spec. weight concrete 157.9 pcf Spec. weight water 62.4 pcf
- 2. Case 2: Spec. weight concrete 150,7 pcf Spec. weight water 63.7 pcf


Phase 1.B: Floating

DRAFT 9.8 ft FREEBOARD 6.2 ft KEELCLEARANCE 13.2ft











Greenup L&D Miter Gate Bay







Environmental Conditions for Marine Operations

- Mean wind speed below 35 mph
- •Temperature above 35°F
- No fog
- Water velocity considerations
- Water level considerations

































Greenup L&D







Greenup L&D













Braddock Dam TOWBOAT

- Capacity 2100 2600 hp
- Similar to 35 short ton BP tug VESSEL DIMENSIONS
- Braddock = 104' X 333'
- Greenup = 105' X 188'


Greenup L&D Miter Gate Bay






0' 100








Greenup L&D






Greenup L&D







Greenup L&D Miter Gate Bay




R.C. BYRD DRY DOCK























Greenup L&D Miter Gate Bay




R.C. BYRD LOCKS AND DAM








Greenup L&D Miter Gate Bay






RIVER TOW


•Distance 60 miles (52 nautical miles)

•Avarage speed 5 to 6 mph

•Duration 12 to 16 hours (schedule 24 hrs)


Ohio River: R.C. Byrd to Greenup







Greenup L&D Miter Gate Bay



60 miles

NP: EL. 515'

497'

RIVER TRANSPORT

Dredge 1ft or tow at normal pool +1ft



DRAFT 10.0 ft
FREEBOARD 6.0 ft
KEELCLEARANCE 3.0 ft

Phase 2: River Transport







Greenup L&D Miter Gate Bay




Cofferdam & Nose Cell Constructed




























































































































Phase 3: Arrival at floating construction site



Greenup L&D
Miter Gate Bay






Phase 3A: CONSTRUCTION deck BF_39

DRAFT 11.5 ft FREEBOARD 5.5 ft KEEL CLEARANCE 15.5ft









Greenup L&D

Miter Gate Bay




Protective Barge




Spacer pontoons

Pontoons 40'x 8'x 8'


Cofferdam






Mooring Configuration During Floating Construction








Greenup L&D Miter Gate Bay




Phase 3C: SHAFTS, height 16-31 ft, incl. bulkheads















Phase 3E: Ready for Immersion






Mooring Configuration During Floating Construction




Greenup L&D Miter Gate Bay




Start Ballasting at Deep Draft Location

























Pitching Set-Down Guide



Greenup L&D Miter Gate Bay




Downstream Middle Wall

Final Position

Set-Down Guide

Installation Tolerances








Water Ballast System







Greenup L&D Miter Gate Bay






Piping Water Ballast System


Great Belt Bridge Denmark - Installation Pylon Caisson



Immersion and Set Down








Phase 4A: Touch down at NP EL 485'


Waterballast (case 2) Max. immersion speed 7,200 T 3 ft/hr





























Greenup L&D Miter Gate Bay






1000 MT Elastomeric bearing











Greenup L&D

Project Milestones (with 07 CG Start)

- Mooring Cells Construction 2007 to 2009
- Miter Gate Fabrication 2007 to 2009
- Lock Extension Construction 2010 to 2012
- Rehab Main Chamber 2012 to 2014
- Total Project Completion 2014



U.S. Army Corps of Engineers
Huntington District
502 Eighth Street
Huntington, WV 25701
(304) 399-5170
rodneyc@lrh.usace.army.mil