



US Army Corps
of Engineers
Louisville District



U.S. Army Corps of Engineers

Louisville District

Olmsted L&D, Dam

In-the-wet Construction

Byron McClellan, P.E.
Dale Berner, PhD, P.E.
Kenneth Burg, P.E.



US Army Corps
of Engineers
Louisville District

Olmsted Locks & Dam Project

1996 rendering of completed project






**US Army Corps
of Engineers**
Louisville District



Navigation Projects Ohio River

KY, IL, IN, OH, WV and PA





US Army Corps
of Engineers
Louisville District

Olmsted Dam Cost Reimbursable Contract



Contractor: Washington Group/Alberici

Award: 31 March 2004

Estimated Cost: \$564,148,484.00

Completion Date: 30 November 2011



US Army Corps
of Engineers
Louisville District



Olmsted Dam Cost Reimbursable Contract *(Cost –Plus- Award Fee)*

- ***Risk is shared***
- ***Collaboration:***
 - Contractor***
 - Design AE***
 - Corps***
- ***Work is Controlled with “WAD’s”***
- ***Items purchased are Corps’ Property***
- ***Contractor’s Award Fee based upon performance.***



US Army Corps
of Engineers
Louisville District

Brief History

Dam Construction Studies



- ***Cellular Cofferdam***
- ***Braced Single – Wall Cofferdam***
- ***Mobile Cofferdam***
- ***In - the - Wet Construction***



US Army Corps
of Engineers
Louisville District



In – the – Wet Construction


- ***Pre-cast Shell Construction***
 - *On – site casting yard*
 - *Marine way to lower shells to river*
 - *Lifting frames to stiffen shells*
- ***Foundation Prep In – the – Wet***
- ***Set shells with catamaran barge***
- ***Fill shells with tremie concrete***
- ***Set Tainter Gates***



US Army Corps
of Engineers
Louisville District




Precast Yard





US Army Corps
of Engineers
Louisville District


Dam





US Army Corps
of Engineers
Louisville District


Catamaran with Lower Pier Shell





US Army Corps
of Engineers
Louisville District


Placement of Upper Pier Shell Elements





US Army Corps
of Engineers
Louisville District

Tremie Concrete Sequence






US Army Corps
of Engineers
Louisville District



Tainter Gate






US Army Corps
of Engineers
Louisville District




Wicket Assembly





US Army Corps
of Engineers
Louisville District

Relative Scale





US Army Corps
of Engineers
Louisville District

Dam Site May 2005





US Army Corps
of Engineers
Louisville District



Original Scope

- + Government only provided conceptual design on means and methods. Gave Contractor considerable latitude to propose changes.
- + Government if requested would provide design engineer to finish conceptual designs (means and methods) or redesign features of work if contractor had a better idea.



US Army Corps
of Engineers
Louisville District

2005 Infrastructure Systems Conference



***Design Changes to Tainter Gate Shells
for
Super Gantry Method of Construction
at***

***The Olmsted Dam Project
Jacobs / Gerwick - A Joint Venture
in Partnership With
The Louisville District, COE***

Presented By: Dale Berner, PhD, PE



US Army Corps
of Engineers
Louisville District

Differences between the Initial and the Super Gantry Construction Methods



■ **INITIAL Plan**

- ***Precast Elements for Building the Shells.***
- ***Shells Built on Sleds.***
- ***Shells Can Only be Lifted Submerged.***
- ***Tremie Reinforcing Mats Pre-Installed.***
- ***Uses Temporary Scour Articulated Concrete Mats***
- ***Tremie from Floating Plant.***


■ **SUPER-GANTRY PLAN**

- ***The Shells Are Cast-in-Place.***
- ***Shells Built on Slabs.***
- ***Shells Can be Lifted In-the-Dry.***
- ***Tremie Mats Lifted-in with the Shells.***
- ***Uses Permanent Grout Mats for Scour Control.***
- ***Tremie from Land Plant.***



US Army Corps
of Engineers
Louisville District

Initial Precast Yard Concept



MARINE SKIDWAY


LANDBASE SKIDWAY

PRECAST BEDS



US Army Corps
of Engineers
Louisville District

Super Gantry Casting Bed Alignment





US Army Corps
of Engineers
Louisville District

Preparation for Marine Skidway





US Army Corps
of Engineers
Louisville District

Typical Casting Slab on Grade





US Army Corps
of Engineers
Louisville District

Preparation for Pile Supported Casting Slab






US Army Corps
of Engineers
Louisville District


Casting Sequence for Tainter Gate Shells




Year 1



Year 2



Year 3






US Army Corps
of Engineers
Louisville District


Casting Sequence for Navigable Pass Shells




Year 4



Year 5




Year 6





US Army Corps
of Engineers
Louisville District


Localized Supplemental Reinforcing in a Typical Slab





US Army Corps
of Engineers
Louisville District


Common Types of Shells and Tremie Mat Templates





US Army Corps
of Engineers
Louisville District


Typical Template for Tremie Concrete Reinforcing Mat





US Army Corps
of Engineers
Louisville District


Typical Tremie Rebar Mat on Template





US Army Corps
of Engineers
Louisville District


Typical Cross-Section of Tremie Rebar Mat on Template





US Army Corps
of Engineers
Louisville District


Typical Shell Lifted By Super Gantry Crane onto Tremie Mat





US Army Corps
of Engineers
Louisville District

Typical Shell / Rebar Mat / Template on Marine Skidway Cradle






US Army Corps
of Engineers
Louisville District

Cradle for Marine Skidway




Marine Rails





US Army Corps
of Engineers
Louisville District

Plan View of Catamaran Crane Barge & Snubbing System




FLOW →



US Army Corps
of Engineers
Louisville District



Profile View of 5,000 tons Catamaran Crane Barge & Snubbing System






US Army Corps
of Engineers
Louisville District



5,000 TONS Catamaran


Lowering Tainter Gate Sill Shell





US Army Corps
of Engineers
Louisville District


Erection of Pre-Fabricated Tainter Gate





US Army Corps
of Engineers
Louisville District


Navigable Pass Section of Olmsted Dam





US Army Corps
of Engineers
Louisville District


Sequence of Construction for Navigable Pass





US Army Corps
of Engineers
Louisville District


Typical “Controlled Moment” Pile Connection





US Army Corps
of Engineers
Louisville District


Typical Landing Pile with Flat-Jacks





US Army Corps
of Engineers
Louisville District

Sequence for tremie Concrete Placement for Navigable Pass



STAGE 1 POUR

**STAGE 2
POUR**




US Army Corps
of Engineers
Louisville District

Typical Elevation of Navigable Pass



PAVING BLOCK



CONTROLLED FIXITY PILES



US Army Corps
of Engineers
Louisville District

2005 Infrastructure Systems Conference



***Design Changes to Tainter Gate Shells
for
Super Gantry Method of Construction
at***

***The Olmsted Dam Project
Jacobs / Gerwick - A Joint Venture
in Partnership With
The Louisville District, COE***

***Presented By: Ken Burg
Project Manager***




US Army Corps
of Engineers
Louisville District

Major Project Components



Illinois




Kentucky



US Army Corps
of Engineers
Louisville District

Tainter Gate Section





US Army Corps
of Engineers
Louisville District

Precast Shell Statistics



- ***Sill Shells***
 - ***125' x 102' x 30', 3683 tons dry, 2151 tons wet***
- ***Stilling Basin Shells***
 - ***125' x 116' x 18', 3647 tons dry, 2130 tons wet***
- ***Lower Pier Shells***
 - ***102' x 69' x 14', 2112 tons dry***
- ***Upper Pier Shells***
 - ***57' x 30' x 14', 601 tons dry; will be cast in place with this method***



US Army Corps
of Engineers
Louisville District

Original Method of Construction



- *Prepare in-the-river foundation, complete with piles and tremie reinforcing mat*
- *Cast shells on shore, self weight fully supported*
- *Move shells into water, self weight fully supported*
- *Pick up and transport shells submerged*
- *Set shells in place on prepared foundation and fill with tremie concrete*



US Army Corps
of Engineers
Louisville District

Super Gantry Method of Construction



- *Prepare in-the-river foundation and drive piles*
- *Cast shells on shore, self weight fully supported*
- *Attach lift frame to shells and remove secondary shoring*
- *Lift shells in-the-dry and mate with tremie reinforcing on skidway*
- *Move shells into river and transport partially submerged*
- *Set shell and tremie reinforcing over piles and fill shells with tremie concrete*



US Army Corps
of Engineers
Louisville District

Changes in Design Requirements



- *In-the-dry lift increases load to shells and lift frames by a minimum of 70%*
- *Transport is partially submerged; center of gravity of lift changes during setdown; loads to catamaran barge increase*
- *Connections between shell / lift frame and between lift frame / catamaran are much larger*
- *Shell geometry and reinforcing revised for increased loading*



US Army Corps
of Engineers
Louisville District

Revisions to Shells for Super Gantry - 1



- *Increase dimensions of selected stiffening elements to accept additional reinforcing / maintain existing reinforcing*
- *Increase size / decrease spacing of selected reinforcing*
- *Revise intersection of typical stiffening element for larger connection to lift frame*
- *Increase “gap” between shells for increased clearance at set down*
- *Revise continuity reinforcing to include portions of tremie reinforcing*
- *Revise tremie reinforcing to clear casting supports*



US Army Corps
of Engineers
Louisville District

Revisions to Shells for Super Gantry - 2




- *Revise (shorten) training walls on SBS-6 shell to clear larger catamaran*
- *Revise connection between Sill Shell and Lower Pier Shell for reinforcing assembly in-the-dry after mating and dewatering*
- *Revise underdrain details and location to clear splice location between shell continuity bars and tremie reinforcing mat*



US Army Corps
of Engineers
Louisville District


Revise Training Wall on SBS Shell





US Army Corps
of Engineers
Louisville District


Revise Training Walls on SBS Shell





US Army Corps
of Engineers
Louisville District


Revised Sill to Lower Pier Connection





US Army Corps
of Engineers
Louisville District

Revisions to Shells for Super Gantry



REBAR CODE

- 1. Green rebar is shell continuity reinforcing
- 2. Blue rebar is tremie rebar mat reinforcing

Notes:

- 1. Typical at SS-1 to SS-2, SS-3 to SS-4 and SS-5 to SS-6
- 2. At Contractor's option, install with shell continuity bars or tie to shear reinforcing and position after mating shell and rebar mat.
- 3. Using spliced bars from S-72, rotate bars back and position after shell is mated to rebar mat.
- 4. At Contractor's option, install with continuity bars or pullback and position after shell mating with rebar mat.

SS to SS INTERFACE



US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry





- ***Configure Lift Frames for SBS-1 for reuse with SBS-6 with minimum rework***
- ***Revise connection between shell / frame to meet Contractor preferences for location and orientation***
- ***Add man door to bottom of leg for personnel access to assemble shell/frame connection; reinforce leg***
- ***Add full area access platforms to top of lift frame to meet Contractor work plan***
- ***Revise wall thickness and material strength for selected leg members to match demands from increased loadings***




US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry





Shell SBS-1






US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry





Shells SBS-2 thru SBS-5






US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry






Shell SBS-6





US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry






Shell SS-1



US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry






Shells SS-2 thru SS-5



US Army Corps
of Engineers
Louisville District

Revisions to Lift Frames for Super Gantry



Shell SS-6



US Army Corps
of Engineers
Louisville District

Summary



- ***The Super Gantry Method of Construction required re-analyses of the shells and lift frames for loadings approximately 70% greater than the original design***
- ***Modifications to the shells and lift frames have been included almost entirely within the geometric envelope of the original design***
- ***The sequence of work has been modified drastically compared to the visible modifications to the shells and lift frames***
- ***The Super Gantry Method of Construction provided the Contractor with the benefits of reduced operation time in the river with more mating operations completed on shore in-the-dry***



US Army Corps
of Engineers
Louisville District



Byron McClellan,
USACE-Louisville District
502-315-6240

Byron.K.McClellan@LRL02.usace.army.mil