




Replacing Existing Lock 4: Innovative Designs for Charleroi Lock

**LISA R. PIERCE, P.E.
DAVE A. STENSBY, P.E.**
Project Managers
INCA Engineers, Inc.

STEVE R. STOLTZ, P.E.
Project Engineer
Pittsburgh District, USACE

PROJECT LOCATION & EXISTING LOCK 4



TRI-SERVICE INFRASTRUCTURE SYSTEMS CONFERENCE - 2005

INCA



PITTSBURGH
DISTRICT

EXISTING LOCK 4




TRI-SERVICE INFRASTRUCTURE SYSTEMS CONFERENCE - 2005

INCA




PITTSBURGH
DISTRICT


PLAN VIEW - EXISTING LOCK 4




PLAN VIEW – EXISTING & NEW LOCK WALLS WITH COFFERBOX MONOLITHS INDICATED




PLAN VIEW – NEW CHARLEROI LOCK




TYPICAL COFFERBOX



CROSS SECTION - RIVER WALL COFFERBOX




PLAN VIEW - TREMIE CONCRETE PARTITION




COFFERBOX CONSTRUCTION

Location of Typical Example (Steps 1 - 7)




COFFERBOX CONSTRUCTION

Step 1




COFFERBOX CONSTRUCTION

Step 2




COFFERBOX CONSTRUCTION

Step 3




COFFERBOX CONSTRUCTION

Step 4




COFFERBOX CONSTRUCTION

Step 5




COFFERBOX CONSTRUCTION

Step 6



COFFERBOX CONSTRUCTION

Step 7



CONSTRUCTION COST



Charleroi Locks, Contract One (River Wall)

Trumbell and Brayman Construction JV
\$96.5 Million Construction Award

September 2004

CONTRACTOR INPUT



Excavation within Cofferdboxes

- Shaft casing and strut obstructions
- Feasible (less congested than other completed projects)
- Prefer excavating after casings are installed
- Clamshell, air-lift, and dredge pump

CONTRACTOR INPUT



Formwork and Access Requirements

- Distance between inside face of cofferbox and finished face of monolith = 3' – 6" (contractors said a minimum of 2 to 3 feet needed)
- Additional space available for personnel in AZ pile recesses
- Walers do not encroach on this space (upper walers – exterior, lower walers – removed prior to forming)
- River wall access from river side
- Middle wall access – temporary work platform on top of cofferbox

CONCLUSION



✓ Cofferdboxes are well-suited for:

- New sites
- Sites where new locks are offset from navigation traffic and existing locks

Otherwise, cofferboxes reduce navigation width available during construction.

✓ Advantages of construction in local cofferboxes

- Elimination of conventional global cellular cofferdams
 - Reduces total construction time and costs
 - Reduces navigation impacts
 - Reduces hydraulic impact on waterway
- Monolithic concrete construction



**Thank
You**



TRI-SERVICE INFRASTRUCTURE SYSTEMS CONFERENCE - 2005

INCA



PITTSBURGH
DISTRICT

**TRI-SERVICE
INFRASTRUCTURE SYSTEMS
CONFERENCE - 2005**

**LISA R. PIERCE, P.E.
DAVE A. STENSBY, P.E.
Project Managers
INCA Engineers, Inc.
L.Pierce@incainc.com
D. Stensby@incainc.com
(425) 635-1000**

**STEVE R. STOLTZ, P.E.
Project Engineer
Pittsburgh District, USACE
Stephen.R.Stoltz@LRP02.usace.army.mil
(412) 395-7297**