



Nonlinear Incremental Thermal Stress Strain Analysis Portugues Dam

Thermal Analysis Project Team

David Dollar Project Manager (USACE, Jacksonville District)

Ahmed Nisar (MMI Engineering)

Paul Jacob (MMI Engineering)

Charles Logie (MMI Engineering)


2005 Tri-Services Infrastructure Conference August, 2005







Objectives of Study

- Long term stable temperature response
- Location and behavior of contraction joints
- Potential for cracking
- Significance of material properties




NOTE:
 1. VOLUME OF DAM = 387,141 CU. YDS.
 2. CONTOURS DEPICT ASSUMED TOP OF ROCK.



UPSTREAM ELEVATION DEVELOPED LOOKING UPSTREAM SCALE: A

110'-00"

REFERENCE PLANE SCALE: B







Project Approach

- **Phase I - Preliminary Analysis**
 - Model testing (concurrent with dam design)
 - Parametric study to determine significant parameters
- **Phase II – Final Analysis**
 - Final dam geometry
 - Final material properties

Analysis Procedure






Analysis Approach


(ETL 1110-2-365)

- De-coupled thermal/stress analysis using ABAQUS/Standard
- Combination 2D and 3D analysis
- Incremental placement of lifts
- Material nonlinearity
- Boundary conditions

2D Dam Geometry




3D Dam Geometry



Thermal Material Properties




- Roller compacted concrete
 - Non linear internal heat generation (heat of hydration from adiabatic temperature rise)
 - All other properties linear (C_p , k , γ)
- Linear (uniform) foundation material



$$\dot{H} = \gamma \cdot C_p \cdot \frac{\Delta\theta}{\Delta t} \quad (\text{BTU/in}^3/\text{day})$$

Structural Material Properties

- General nonlinear properties for RCC
 - Modulus
 - Shrinkage
 - Creep/Aging
- Linear foundation material






Boundary Conditions


- Thermal analysis
 - Time/temperature dependent transfer films
 - Solar radiation flux
 - Heat loss to foundation
- Structural analysis
 - Foundation constraint
 - 3D Model - contact at construction joints




Average Solar Radiation (1961-1990)
(every hour for 365 days)



Average Data (1961 - 1990) 15th Day of Each Month
Global Horizontal (Normalized to Max)




15th Day of 2004 Normalized to Max Temp of the Day





Phase I Example Results

Run 2
monthly temperature variation
without solar radiation



Run 10
monthly temperature variation
with solar radiation



1-Year After Construction

End of Construction


Lift 200

Lift 150


Lift 100

Lift 50



Phase I Example Results












(a) Solar Radiation not Included (Run 2)



(b) Solar Radiation Included (Run 10)



Phase I Example Results





Simplified Analysis

- Tatro & Schrader
- ACI 207.2R-95
- ETL 1110-2-542

Simplified Thermal Analysis of Portugues Dam

Structural Properties

Crest length X	1,298.1 ft	15,577 in
Cross section length L	110 ft	
Cross section height H	220 ft	
L/H	0.5	
A_f/A_g	2.5	

Monthly Average Temperatures

January	75.0 °F
February	75.2 °F
March	75.7 °F
April	77.1 °F
May	78.9 °F
June	80.4 °F
July	80.9 °F
August	80.8 °F
September	80.2 °F
October	79.5 °F
November	77.9 °F
December	75.8 °F
Average	78.1 °F

RCC Thermal Properties

Adiabatic temperature rise T_{ad}	48 °F (25+ days)
Specific heat C_p	0.234 BTU/lb-°F
Conductivity K	1.835334 BTU/in-day-°F
Diffusivity h^2	3.5 in ² /hr
	0.024 ft ² /hr

Thermal Data

RCC placement temperature T_i	78.1 °F
Final stable temperature T_f	78.1 °F
(Assume the internal mass will cool to the average annual temperature)	

Induced strain


Long term temperature change $dT = T_f + T_{ad} - T_i$	-48.0 °F
Induced strain $\epsilon = C_T dT K_R K_f$	2.02E-04
Cracking strain $\epsilon_{cr} = \epsilon - \epsilon_{sc}$	9.50E-05
Total crack width (shrinkage) $cw_{total} = \epsilon_{cr} L$	1.48 in
Assumed crack width (cw)	0.125 in
No of cracks $N = cw_{total}/cw$	11.84
Average crack spacing $S = X/N$	109.6 ft

RCC Mechanical Properties

Coefficient of thermal expansion C_T	4.2E-06 /°F
Weight density w_c	0.09285048 lb/in ³
Tensile strain capacity ϵ_{sc}	1.065E-04
Modulus of elasticity RCC E_c	4.30E+06
Modulus of elasticity foundation E_f	3.70E+06

Restraint Factors





Compute restraint factors (Y or N)?	n
h/H	0
Structural restraint factor K_R	1.00
Foundation restraint factor K_f	1.00



$$K_R = \left(\frac{\frac{L}{H} - 2}{\frac{L}{H} + 1} \right)^{3/4} \text{ for } L/H \geq 2.5$$


$$K_R = \left(\frac{\frac{L}{H} - 1}{\frac{L}{H} + 10} \right)^{3/4} \text{ for } L/H < 2.5$$

$$K_f = \frac{1}{1 + \frac{A_g E_c}{A_f E_f}}$$





Note: $K_f = K_R = 1$, if not specified on the graph

Results Status (Phase II) - Thermal



Results Status Phase II - Stress










Remaining Steps

- Thermal component of analysis are nearing completion
- Stress analysis
 - Construction sequence completed
 - Long term cool down requires coarser mesh to achieve adequate computational performance
- Coarse mesh mapping of thermal results is underway – reasonable comparison is being obtained


Mesh Mapping Methods



2
| stress analysis using fine mesh



2
| stress analysis using coarse mesh



30 coarse mesh



Analytical Management

- Management of model size
 - Geometry (lift size)
 - Load time step resolution (solar radiation/daily temperature variation)
 - Long duration for dam cool down (years rather than months)
- 3rd party material model usage
 - It would be more convenient to use an internal material model in ABAQUS



Analytical Management

- Software bugs
 - Debugging vendor software
 - Memory management issues
(porting of software to non native platforms)
- Software limitations (and workarounds)
 - Mesh mapping to reduce computational overheads of stress analysis phase of work
 - Selection of contact algorithms