Marine Corps Operational Test and Evaluation Activity



Interpreting Reliability and Availability Requirements for Network-Centric Systems



What MCOTEA Does



Multi-service Test Quick Reaction Test Test Observations



Purpose

 To engage test community in a discussion about methods in testing and evaluating RAM for software-intensive systems



Software-intensive systems

- U.S. military one of the largest users of information technology and software in the world [1]
- Dependence on these types of systems is increasing
- Software failures have had disastrous consequences

Therefore, software must be highly <u>reliable and</u> <u>available</u> to support mission success



Interpreting Requirements

Excerpts from capabilities documents for software intensive systems:

Availability

"The system is capable of achieving a threshold operational availability of 95% with an objective of 98%"

"Operationally Available in its intended operating environment with at least a 0.90 probability"

Reliability

"Average duration of 716 hours without experiencing an operational mission fault"

"Mission duration of 24 hours"

"Completion of its mission in its intended operating environment with at least a 0.90 probability"



Defining Reliability & Availability

What do we mean reliability and availability for software intensive systems?

- One consideration: unlike traditional hardware systems, a highly reliable and maintainable system will not necessarily be highly available
 - Highly recoverable systems can be less available
 - A system that restarts quickly after failures can be highly available, but not necessarily reliable
- Risk in inflating availability and underestimating reliability if traditional equations are used.
- Perhaps "dependability" is a better term [2]




Interpreting requirements

What do we mean by failures?

- One interpretation: flaws in code or software "bugs"
- Challenges:
 - Impractical to test all possible code combinations in CT, DT or OT
 - A relatively simple system with 20 inputs, each with 10 possible values
 = 10²⁰ possible combinations of settings ^[3]

Examples of code failures:

- Mars Pathfinder
- USS Yorktown
- Ariane 5 rocket
 (European Space Agency)




Code failures

Since code failures are deterministic

- Pseudo-exhaustive testing
- C(20,4) = 20!/4!(20-4)! = 4,845
- C(20,6) = 38,760



- E.g., ACTS from NIST
- Algorithms to produce smaller test sets





Stochastic failures

- Bandwidth variability
- User in the loop
 - Operator should be viewed as system components
 - Training
 - Crew-caused errors





Failure to interpret requirements

Number one cause of software failures [1]

- Inadequate specifications
- Misconceptions about requirements
- Serious usability flaws
- These flaws are often overlooked, and users are unfairly blamed [1]

Examples of lethal consequences from poor designs:

- Precision Lightweight GPS Receiver (PLGR)
- Therac-25 radiotherapy machines



Solutions



Equations

Measure and report reliability and availability from different perspectives

Availability:

Mission availability (availability over time)

$$A_{m} = \frac{\mu}{\lambda + \mu} - \frac{\lambda}{(\lambda + \mu)^{2} T} \exp[-(\lambda + \mu)T]$$

IT availability (time independent)


$$A_{IT} = \frac{\text{#successful attempts to access system}}{\text{#total attempts}}$$

Reliability:

- $R_{IT} = 1 (Sum_i f_i/n_i * P(Z_i))^{[5]}$
- $R(t) = e^{-\lambda t}$

Dependability:

• $D_s(t; \tau) = A_s(t) * R_s(t, \tau)$ [2]



Availability as a function of operating time [6]



Measure at different nodes

- User level
- Server level
- Unit level
- Report on each, plus:
 - Level of degraded service
 - May have to "script" some tests to ensure breadth of mission scenarios covered

Microsoft uses similar methods to test expected operations over a randomized schedule over a smaller interval of time [6].

(i.e., Accelerated Life Testing)



Integrated Testing

- Partner with developmental testers
 - Ensure detection of code failures
 - Early user evaluations
- Early dialogue with requirements documents generators
 - Critical to ensure systems are built right for intended missions
 - Solicit clear guidance on definitions of reliability, availability and dependability



References

- 1. National Academy of Sciences. 2007. Software for Dependable Systems: Sufficient Evidence? Jackson, D. Thomas, M. and Millett, L.I., Editors, Committee on Certifiably Dependable Software Systems, National Research Council.
- 2. Heddaya and Helal, 1996. Reliability, Availability and Dependability: A user-centered view. Boston University White Paper BU-CS-97-011
- 3. Kuhn, D.R., Kacker, R.N., and Lei Y. 2010. Advanced Combinatorial Test Methods for System Reliability. Reliability Society 2010 Annual Technical Report.
- Kuhn, D.R., D.R. Wallace and A.M. Gallo, Jr., 2004. Software Fault Interactions and Implications for Software Testing, IEEE Transaction on Software Engineering. Vol 30, No. 6.
- 5. ATEC. 2004. Reliability, Availability, Maintainability (RAM) Concept Information Technology. July 14, 2004 brief. 5. Donald MacKenzie, 2001, *Mechanizing Proof: Computing, Risk, and Trust, MIT Press, Cambridge, Mass.*, Chapter 9.
- 6. Nicholson, C.D., Tsang, M.Y., Zhao, Z., Zhou, H. 2003. System and Method for Testing Software Reliability over Extended Time. United States Patent No.: US 6,557,120 B1.



Questions

Jeanne Hartzell

Jeanne.hartzell@usmc.mil

Visit our website at www.mcotea.marines.mil