















2017 NDIA Armament Systems Forum Firing Demonstrations (Session III)

LTC John Masternak
Product Manager, Small Caliber Ammunition
1-4 MAY 2017



Agenda



- Small Caliber Portfolio
- 7.62mm RDT&E Overview
 - XM1161 7.62mm One Way Luminescence (OWL)
 - XM1165 Reduced Range Ammunition (RRA)
 - Lightweight (LSCA)
- .50 Cal All-Purpose Tactical Cartridge (APTC) & RRA Overview
- Green Primer Overview

PM Reliable, Precise, Lethal MAS

Small Caliber Ammunition Family



M17 Trace M20 API-T

.22 Long 12 Gauge M1030 M1041 M1071 M1042

| RELIABLE - | PRECISE - | LETHAL

Shotshells

M8 M211 MK257 M263 M962 M903 M860 M858
API API API-DT AP SLAP-T SLAP Tracer Ball
DISTRIBUTION STATEMENT A:
Approved for Public Release; Distribution is unlimited

.50 Cal.



7.62mm Lightweight Small Caliber Ammunition (LSCA)



Description:

 7.62mm Lightweight Small Caliber Ammunition (LSCA) is project to replace brass in conventional ammunition cases with the main goal of reducing Soldier and weapon platform load to improve mobility

- Top Level Strategy:

- Three phase contract execution to identify Technology, design maturity and downselect in preparation for VT&PVT
- Small Caliber producers will assist Case supplier to design in preparation for scale up Manufacturing and reduced risk through FY18 to down-select to one concept
- Phase II Contract award (Type and vehicle TBD) in 4QFY17

Recent Milestones & Events:

- Prototype Technology Readiness Assessment (TRA) completed at ATC (4QFY16)
- Material Analysis of M80 Polymer Cartridge Case (4QFY16)
- Conducted Phase I Industrial Impact Study final briefing (3QFY17)

Future Milestones & Events:

- Conduct Joint Lightweight IPT Review (3QFY17)
- Conduct CRADA TRA testing at ATC (4QFY17)
- Award Phase II contract (4QFY17)

Risk Areas:

- Temperature Sensitivity (Technical)
- Weapon/Ammo Interface (Technical)
- Proprietary Design and Manufacturing Process (Cost)
- Technology maturity & transition to LCAAP (Schedule)



																	mata	,					(00	,				
		FY	16			FY					18			FY					20			FY				FY2		
	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q
MILESTONES/ PHASES		Indu	stry D	ay			I		SR	R	TIW	G PDR						CD	R		Dec	ision I	Point			Field	ling	
CONTRACTS							I I A	ward	Phase	II					A	ward I	hase	II				 	ECP	Awar	d			
ENG./TECH REVIEWS						M	cure. Allo Lead Tim lanTech rement	Phase 1b - ManTech LCAAP			Phase VanTec cremen	:h					Pha	se III					Fieldi	LRIP			>	
TEST			TRL Ev	al. .cc. Ag	ing		1		TRL Eval						PVT LUE				i ! ! !	\ 	/T	İ	O.					
DELIVERIES (QTYS)		1	35K 8K				1	2	K					50K	/50K				500	OK		 			1.8M			





XM1161 7.62mm One Way Luminescence (OWL)



Description:

- Replaces current tracer with OWL that reduces signature to enemy preventing localization of shooter
- Incorporated into EPR base projectile to increase tracer round effects on target





Top Level Strategy:

- DOTC and ARDEC prototype development through TRL 6 Assessment
- ARDEC tech maturation and risk reduction through FY18 to design down-select to one OWL design
- Contract award (type and vehicle TBD) in 2QFY19 for EMD

Recent Milestones & Events

- 1QFY17 MDA Delegation approved
- 2QFY17 MDD

Future Milestones & Events

- 4QFY17 TRL 6 Assessment
- 1QFY19 PDR and Down-Select
- 1QFY19 MS B
- 2QFY19 EMD Contract Award

Risk Areas

- Meeting maturity for TRL 6 (visibility angle and distance) (Performance)
- Manufacturing design of tracer cavity in M80A1 projectile to minimize ballistic performance deviation from ball round
- (Cost/Technical) Manufacturing process to reduce cost and eliminate steps in tracer cartridge production
- (Technical) Maintaining tracer performance and consistency during manufacturing scale up

	FY	17			FY	18		FY	19			FY	20			FY	21			FY	22		FY	23	
1Q	2Q	3Q	4Q	1Q	2Q	3Q 4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q 4C	1Q	2Q	3Q	4Q
M	DD						M	\$ B										P	MS C /		TC-STD /	,			
		- -				Draft RFP	RFP	Awar	d	EM	D (KTR	Faciliti	zation,	Machi	ne Prov	e-out)			LRIP Option		FI Op	RP ion	5	>	
							V D		t													d			
	ļ	٠.	TRA / T	RL 6 emo			PDR			! ! !		CD	К								<u></u>				
	DT			AF	RDEC T	esting D	VT				PPQT UA				E	PQT LFTE					616				
										100k					500K								:		
	M Govt	MDD Govt / Ind Co Developme	MDD Govt / Ind Concept Development	1Q 2Q 3Q 4Q MDD Govt / Ind Concept Development TRA/T	1Q 2Q 3Q 4Q 1Q MDD TMRR (Govt / Ind Concept Development TMRR (TRA/TRL 6 Tech. Demo	Govt / Ind Concept Development TRA/TRL 6 Technol Track	1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q MDD Draft RFP Govt / Ind Concept Development TRA / TRL 6 Tech. Demo	TRA/TRL6 DT ARDEC Testing DVT ARDEC Testing DVT 12K per	MDD	TMRR (ARDEC Dev of 3 OWL Design Down select TRA/TRL6 Technologies) DT ARDEC Testing DVT 12K per	1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q	1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q MDD MSB EMD (KTR Award Draft RFP RFP Technologies) DT ARDEC Testing DVT PPQT UA	1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q MS B EMD (KTR Facilities Award Development TMRR (ARDEC Dev of 3 OWL Design Down select TRA/TRL6 Technologies) DT ARDEC Testing DVT PPQT UA 12K per Concept Conc	1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q MNS B EMD (KTR Facilitization, Award Development Technologies) TMRR (ARDEC Dev of 3 OWL Design Down select CDR Development Technologies) DT ARDEC Testing DVT PPQT UA	1Q 2Q 3Q 4Q 1Q 2Q 4Q 4Q 1Q 4Q	1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 2Q 3Q 4Q 1Q 1Q 2Q 3Q 4Q 1Q	1Q 2Q 3Q 4Q 1Q 2Q 4Q 4Q 1Q 2Q 4Q	1Q 2Q 3Q 4Q 1Q 2Q 4Q 4Q 1Q 2Q 3Q 4Q 1Q 4Q 1Q 2Q 3Q 4Q 1Q 4Q 1Q 4Q 4Q 1Q 4Q	1Q 2Q 3Q 4Q 1Q 1Q 2Q 3Q 4Q 1Q 1Q 2Q 3Q 4Q 1Q	1Q 2Q 3Q 4Q 1Q 1Q 2Q 3Q 4Q 1Q 1Q 2Q 3Q 4Q 1Q	1Q 2Q 3Q 4Q 1Q 4Q 4Q 4Q 4Q 4Q 4	1Q 2Q 3Q 4Q 1Q 4Q 4Q 4Q 4Q 4Q 4	1Q 2Q 3Q 4Q 1Q 7C-STD / TC-STD / TCLP / TC	1Q 2Q 3Q 4Q 1Q	1Q 2Q 3Q 4Q 1Q 2Q



7.62mm, XM1164 Reduced Range Ammunition (RRA)



Description:

 Develop and Type Classify advanced ball and tracer training ammunition that more accurately matches trajectory of 7.62mm service ammunition (M80A1)

Top Level Strategy:

- Develop reduced range ammunition that meets Users training requirements
- USG developed prototypes, working with industry on manufacturing requirements
- Full and open single contractor award for EMD in FY19 following successful PDR
- Initial Operating Capability 1QFY23 FMR

Recent Milestones & Events

- RRA Feasibility Study (FY15)
- TRA4 (1QFY17)

Future Milestones & Events

- MDD (2QFY17)
- TRA5 (4QFY17)
- MS B (1QFY19)



Prototype Concept

Risk Areas

- Technology Maturity in S&T (Schedule)
- Max range (Performance)
- Trajectory Match to combat round (Performance)
- Affordability (Cost)

		FY:	17			FY	18			FY	19			FY	20			FY	21			FY	22			FY	23	
	1Q	2Q	3Q	4Q	1Q	2Q	3Q 4	1Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q
MILESTONES/ PHASES			I	DD		Indust	ry	1	MS B											 	A P	MS C			FMR		uction	
PHASES			_լ‴			Day								E	MD P	nase							!	!			- 1	
CONTRACTS			I I			D-RF	Р	RFP Dec.	R	:P	Contr Awa											LRIP						
ENGINEERING/ TECHNICAL REVIEWS		Technolo	I	TRA5		1	Prototypin A SRR	Downs to 1 D	select esign SFF	PD	R					A7CDR				TR	A 8				cie	00	3/	
TEST			į					OVT						PPQ	Ţ				P	QT			, au	.?				
DELIVERIES (QTYS)			5K		5K		30K						50K					5001	K	 			8)					




.50 Caliber RDTE Schedule Overview



7

				20	17			20	18			20	19			20	20			20	21			20	22			20	23	
	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q																				
.50 CAL RRA					4)		
.50 CAL APTC									•			:				:				:				:	: :					



Increase Lethality / Lighten Warfighter Load / Enhance Warfighter Survivability

All Purpose Tactical Cartridge (APTC)

- KSA 1 Lethality APTC: Classified Annex
- KSA 3. Accuracy .50 Cal APTC: .50 caliber APTC must be accurate enough to hit an area target in a 5-7 round burst at 1500m with probability of hit (P/h) of 50% (T) or 2400m with a probability of hit (P/h) of 50% (O)
- Includes <u>OWL</u> & <u>LSCA</u>

ARDEC Concept at TRL3

Improve Warfighter Training

Reduced Range Training Ammo

- KSA 1 Effects-RRA: Maximum range of RRA should not exceed 3,600m (T) or 2,400m (O)
- KSA 3. Accuracy-RRA: RRA must be accurate enough to hit single "E Type" silhouettes representing area target at 900m with 50% probability of hit (T) or at 1500m with 50% probability(O)
- Includes OWL & LSCA


Industry Concept at TRL9; USMC effort to improve performance that will meet or exceed ARMY Threshold requirements





Small Caliber Ammunition Green Primer Path Forward Pre-Dec

				20	16			20	17			20	18			20	19			20	20			20	21			20	22	
	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q	1Q	2Q	3Q	4Q
MIC Green Primer			>				\Rightarrow			>										\(\)								\$		
7.62mm RRA						\														•										
5.56mm M862 SRTA		\ X															:						:						7	
5.56mm / 9mm CCMCK	•			\(\)		:			(X)z							:	:	:					:		:	:				
5.56mm M1037 SRTA																:	:	:			7									



- **Evaluated 5.56mm SRTA cartridges with green primers**
- Selected and qualifying green 5.56mm SRTA M1037 cartridge Ongoing DVT and EMQB
- Benefits soldiers' safety and is environmentally friendly



M1042/M1071/M1041 Close Combat Mission Capability Kit (CCMCK)

- SOCOM is evaluating and qualifying lead free 5.56mm/9mm CCMCK ammunition
- Limited User Demo to include air sampling/toxic fume evaluation at Fort Bragg
- PM MAS will process ECP and modify contract with new lead free NSN/DODIC once qualified



Short Range Training Ammunition

- SOCOM evaluating lead free 5.56mm M862 SRTA that meets performance requirements of M862 SRTA specification (NAMMO) - No Army contract
- 7.62mm SRTA(GD-OTS) currently no effort due to no planned Army buys, only other Services



Reduced Range Ammo (RRA)

Evaluate & Implement either commercial or MIC primer through PPQT/PQT



Metastable Intermolecular Composite (MIC)

- Remove lead from all small caliber ammunition primers
- Develop automated Pilot primer manufacturing process from mixing to packaging
- Upscale pilot process for LCAAP and industry (Risk)
- Provide equal ballistics performance as lead styphnate primers (Risk)



First Deliverables



Small Caliber DOTC Opportunities



AMM-18-01	Prototype projectile and cartridge configurations .50 Caliber and below	evolutionary technological improvements for prototype projectile and cartridge configurations. These configurations represent calibers of .50 caliber and below (including .50 Caliber, .45 Caliber, .38 Caliber, .300 Caliber, 9mm, 7.62mm, and 5.56mm). This program seeks to leverage and develop Non-Developmental Items (NDI), Commercial Off The Shelf (COTS) solutions, and new technology concepts and prototypes that increase range, improve accuracy, reduce weight, reduce cost, or improve health effects for soldiers. Design, development and prototyping efforts can be on any and all components of ammunition or their associated function. Proposed solutions can also include characterization of existing US Army ammunition capability, as it relates to projecting future improvement and prototype development opportunities.
AMM-18-02	Tools, gauges and fixtures	development of prototype tools, gauges and fixtures to support the manufacture and inspection of small caliber ammunition and weapon systems. Calibers of interest include but are not limited to 5.56mm, 7.62mm and Cal 50. Goals of this initiative include prototypes that: 1) reduce size, weight, and complexity of assembly; 2) reduce time and cost of inspection; 3) improve measurement precision and reliability and 4) create a new measurement capability.
AMM-18-03	Tungsten carbide components	assess ability of contractors to fabricate prototype precision tungsten carbide components with tight tolerances and complex geometries.
AMM-18-04	7.62mm ammunition with lightweight metal cartridge cases	development of a lightweight metal cartridge case for the 7.62mm caliber ammunition cartridge, which shall provide a minimum 10% overall cartridge weight saving.
AMM-18-05	Reports, bullets, cartridge cases, test procedures, energetic compositions, and cost models	development and evaluation of prototype solutions to enhance performance, affordability, and environmental effects in small caliber ammunitionalternative components, subcomponents, ancillary components, energetics, and testing materials materials and technology to reduce cartridge effects on the environment and environmental effects on the cartridge such as: corrosion prevention, removal of lead in ammunition systems, solvent-less waterproofing, and mercury replacement.
AMM-18-06	XM1161 small caliber tracer cartridges	development, improvement and manufacture of XM1161 One Way Luminescence (OWL) tracer cartridge. Capabilities of respondents should have ability to complete small scale prototyping with ability to scale tracer line to future full qualification quantities (3,000 cartridges / month to 60,000 cartridges / month)

Enhanced White Papers Due in BIDS by 16 MAY 17